

**AMENDMENTS TO THE CLAIM:**

Claim 1 (currently amended): An improved structure of a long-stick mower essentially comprised of comprising a base, a fixed shear, a mobile shear, a driver, a linkage, [[a]] an extension spring and an extension control rod; wherein, the fixed shear being assembled to [[the]] a bottom of the base; the mobile shear being pivoted to [[the]] a top of the fixed shear by means of a dead spring and a rivet ~~and having at its side at the top an upper side pivoted to the linkage; and another end of the linkage being pivoted to the driver; the linkage having a first end pivoted to an upside of the mobile shear and a second end pivoted to the driver~~, a locking plate provided by [[the]] a side of the driver being pushed up to hold against the base to allow the driver open up backward for the linkage to draw and close the mobile shear in position when the mower is not used, ~~is characterized by that wherein~~ the base [[in]] is approximately an L shape having [[its]] an erected part related to a sleeve fixed to [[the]] a lower end of the extension control rod; the driver ~~with its~~ having a top pivoted to the sleeve of the base and [[its]] a bottom adapted with a caster being drawn towards the base by means of the extension spring and adapted with the locking plate on one side; the extension spring having [[its]] one end hooked to the bottom of the base and the other end drawing the driver; the extension control rod being [[is]] inserted into the sleeve of the base; [[the]] a top of the extension control rod being pressed down for the driver to have [[its]] the caster holding against [[the]] ground and the driver spreading up backward to draw the linkage to move backward to pull the mobile shear for cutting in the direction of facing the fixed shear; then the extension control rod being pulled up for the driver to be drawn back by the extension spring to push the linkage to move forward while pushing the mobile shear to spread up to complete an easy cycle of cutting.